



VpCI®-396 Conductive



PRODUCT DESCRIPTION

VpCI-396 Conductive is a high solids moisture cure urethane for use on marginally prepared structural steel and other metals. It can also be applied on plastic films used in the electronic industry. VpCI-396 Conductive is a single package coating requiring no mixing of multiple packages. The coating may require mixing just before applying the coating to insure that soft settled conductive pigment has been dispersed.

FEATURES

- Consistant conductivity
- Excellent anticorrosion protection
- Single component package
- Can be applied in high humidity and damp conditions
- Can be applied at low temperatures
- Excellent adhesion
- High solids
- Highly abrasion resistant

TYPICAL APPLICATIONS

- Electrical applications
- Conductive metal surfaces

METALS PROTECTED

- Aluminum
- Cast iron
- Steel
- Galvanized steel

ADHESION

- Metals mentioned previously
- Several types of plastics

TYPICAL PROPERTIES

Appearance	Viscous black liquid
Dry to recoat time	Minimum 4 hours at 77°F (25°C) 50% relative humidity
Fully cured	7 days at 77°F (25°C) 50% relative humidity
Maximum time to recoat	2 weeks after initial application (solvent wipe may be required)
Dry to touch time	1 hour at 77°F (25°C) 50% relative humidity
Film hardness	6H to 8H (Pencil hardness)
Flash point	78°F (25°C)
Non-volatile content	36 to 40% by weight
Surface resistance	1x10 ⁴ - 1x10 ⁵ ohms

PACKAGING

VpCI-396 Conductive is available in 5 gallons (19 liters) pails. Keep containers closed when not in use. Storage temperature 40°-75°F (4°-24°C).



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised: 8/7/13. ©Cortec Corporation 2001-2013. Supersedes: 8/3/10. VpCl® is a trademark of Cortec Corporation. © 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.