

EcoShield® S-69 IT



PRODUCT DESCRIPTION

EcoShield S-69 IT is a Vapor phase Corrosion Inhibitor (VpCI®) developed for the water treatment industry. This building block provides corrosion protection for ferrous metals, galvanized steel, aluminum and it's alloys. The VpCIs form a strong monomolecular layer on the metal surface that protects in all three phases- liquid, vapor, and the vapor-liquid interface. EcoShield S-69 IT provides water treatment companies with the ability to incorporate Cortec® VpCI technology into their specific formulations.

The concentration of EcoShield S-69 IT inhibitor in an application can be monitored with UV spectroscopy.

TYPICAL APPLICATIONS

EcoShield S-69 IT Powder is an anticorrosion additive to water treatment formulations to replace chromates, nitrites, borates, and other types of restricted corrosion inhibitors. Powder should be dissolved prior to addition into the cooling system.

DOSAGE RATES

- a) Closed loop-fresh water
Concentration of EcoShield S-69 IT under operating conditions for a closed loop system formulation start at 1500 ppm - 2000 ppm.
- a) Closed loop-brine
Concentration of EcoShield S-69 IT powder under operating conditions for a closed loop system formulation is 1-5 %.
- c) Open loop-fresh water
Concentration varies with formulations but can be used a low as 10-15 ppm in continuous feeds.
- d) Open loop-fresh water-passivation
Concentration of 3000-4000 ppm for 1-2 weeks.

- Protects carbon, stainless, galvanized steels, aluminum, zinc, and other metals
- Prevents corrosion and pitting
- Effective for open and closed loop cooling systems
- Contains contact and vapor phase corrosion inhibitors
- Can be used as a corrosion inhibitor additive in the majority of water treatment programs
- Compatible with the majority of commercially available biocides and antiscalants
- Nitrite, chromate, and heavy metal free
- Readily water-soluble
- Environmentally friendly formula
- Easily traceable with UV spectroscopy

TYPICAL PROPERTIES


Appearance White to off-white powder
pH 9.1-9.6 (1% aqueous)

| ppm in DI Water | Conductivity |
|-----------------|--------------|
| 250 | ~150 µS |
| 1000 | ~600 µS |
| 2000 | ~1120 µS |

FEATURES



Inhibitor Conc. vs. Abs at 230nm



PACKAGING AND STORAGE

EcoShield S-69 IT powders is packaged in 5 lb (2.27 kg) boxes and 50 lb (22.7 kg) and 100 lb (45.3 kg) drums. They should be stored in a tightly closed container. The shelf life is 2 years.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT SAFETY DATA SHEET FOR MORE

INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper



100% post consumer

Revised: 6/10/15 ©Cortec Corporation 2015. All rights reserved. Supersedes: none.
Cortec® and VpCI® are trademarks of Cortec Corporation. ©2015, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.
ISO accreditation applies to Cortec's processes only.