

ATION
USA
FILM
INHIBITOR-PATENT
INHIBITOR



HIGH PERFORMANCE VpCI® PACKAGING

VpCI®-352



PRODUCT DESCRIPTION

VpCI®-352 is a multimetal Vapor phase Corrosion Inhibiting (VpCI®) coating designed for flexible packaging and corrugated board applications. Common applications for coated substrates include interleaving and individual parts wrapping. When metal articles are enclosed within, the VpCI® coating on the substrate vaporizes, reaching all metal surfaces to provide complete corrosion protection. The unique inhibiting action of Cortec® VpCI® forms a very thin and effective protective layer that does not alter the appearance or performance of products or require removal before further finishing or use. Parts protected with VpCI® can be painted, welded, or soldered upon removal from the package.

FEATURES

- No heavy metals, halogens, or solvents
- Nitrite-free
- Provides multimetal protection
- Coated papers are repulpable
- Non-tacky
- Hot melt or cold-set glueable

METALS PROTECTED

- Carbon Steel
- Stainless Steel
- Galvanized Steel
- Cast Iron
- Aluminum and Alloys
- Copper and Alloys
- Silver

METHOD OF APPLICATION

VpCI®-352 should be applied directly to the paper or board with traditional paper coating applicators such as rod, blade, or spray. Drying can be accomplished by passing the coated substrate through a warm air oven or with IR bulbs. Dry coating weights of 3 – 5 lbs/3000 sq. ft. ream (4.9 – 8.2 gsm) are recommended. In applications where long term protection is required or a highly reactive metal will be packaged, heavier coat weights are suggested.

This product is also available in a super concentrated version, VpCI®-352 SC. This can be applied as is or diluted with water to the desired non-volatile content.

TYPICAL PROPERTIES

	VpCI®-352	VpCI®-352 SC
Appearance	Slightly hazy pale yellow liquid	Slightly hazy pale yellow liquid
Non-volatile content	22-28%	39-42%
Density	8.6-8.7 lb/gal (1.03-1.04 kg/l)	8.7-8.8 lb/gal (1.04-1.05 kg/l)
pH	7.4-7.8 (Neat)	7.5-8.0 (Neat)
Odor	Slight	Slight

PACKAGING

VpCI®-352 and VpCI®-352 SC are available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, totes, and bulk.



**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 03/01/17. Supersedes: n/a ©Cortec Corporation 2002-2016 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2016, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.